Improving Water Distribution Network Management through Implementation of Efficient Division into Supply Clusters

by

Tuan Nibras Booso

M.Sc.

2014

DECLARATION

The work described in this thesis was carried out by me under the supervision of Prof. CKM Deheragoda, Department of Geography, University of Sri Jayewardenepura and Mr. HMP Jayantha, Teaching Faculty Member of the M.Sc. Degree in GIS and Remote Sensing, Department of Geography, University of Sri Jayewardenepura and confirm that this has not been submitted in whole or in part to any university or any other institution for another Degree/Diploma.

Signature of Candidate Mr. TN Booso

15/06/2014

Date

DECLARATION OF SUPERVISORS

We certify that the above statement made by the candidate is true and that this thesis is suitable for submission to the University for the purpose of evaluation.

Signature of Senior Supervisor Prof. CKM Deheragoda

. . . .

Signature of Co-supervisor Mr. HMP Jayantha

4100 1 80 1 21

Date

15 08 2014. ... Date

Improving Water Distribution Network Management through Implementation of Efficient Division into Supply Clusters

by

Tuan Nibras Booso

Thesis submitted to the University of Sri Jayewardenepura for the Award of the Degree of Master of Science in Geographic Information Systems and Remote Sensing

15th June 2014

Improving Water Distribution Network Management through Implementation of Efficient Division into Supply Clusters

Tuan Nibras Booso

ABSTRACT

The latest reports revealed that the Non-Revenue Water (NRW) value of the Colombo Municipal Council (CMC) area is in between around 48 - 52 % against the total system supply of 105 - 109 Mm³ of water per annum for 2010 - 2012. Therefore, the National Water Supply and Drainage Board (NWSDB) is considering in reducing the NRW percentage of water distribution volume against the total supply to the system up to 18% or lower value. Today, the international water infrastructure development, maintenance, operation, and construction institutions recognise the District Metered Area (DMA) concept as a suitable method to monitor and operation of water utilities. The accomplishment of such policies has a particular effectiveness at regional scale because of the "local" character of these resources and their positive impacts on socio-economic development and local employment. The minimisation of environmental impact is a further important aspect of the DMA concept.

CMC water distribution network is the oldest and most complicated water distribution network in Sri Lanka and it has been developed and expands slowly for decades. Therefore, finding updated and reliable GIS database of water distribution network is more difficult.

This study presents a GIS methodology including a hydraulic pipe network analysis to find preliminary boundaries to establish the new sub DMAs for the proposed DMAs by the Western Province Metropolitan Area Water Supply Master Plan Update (2013) programme.

Also calculation of the demand for sub DMAs, maintaining minimum pressure of 10m in sub DMAs and optimisation of existing pipes has been done in this study. Originally

proposed 12 numbers of DMAs by the Western Province Metropolitan Area Water Supply Master Plan Update (2013) programme was further subdivided and propose to have total number of 18DMAs from this study. Further the maximum numbers of service connections are limited to 3,500 service connections from this study.

The ultimate result of the study is facilitating the NWSDB with regard to reduce the NRW value in CMC distribution network and manage, operate and maintain the distribution system in a sustainable way in order to provide a more reliable and quality . water supply to the service customers.

ACKNOWLEDGEMENTS

I am gratefully and heartily thankful to my supervisors, Prof. CKM Deheragoda and Mr. H. M. Prabath Jayantha, for their guidance, support, understanding, patience and most importantly, their encouragement that enabled me to make this research successfully.

Also I am very much grateful to all the Lecturers, Instructors of the MSc degree programme in GIS and Remote Sensing and the staff of the Postgraduate Institute of Science, for the great support and guidance throughout the whole course.

I am grateful to my employer, the National Water Supply and Drainage Board (NWSDB) and especially to staff of project management unit of Greater Colombo Water and Wastewater Management Improvement Investment Programme (GCWWMIIP), and special thanks to Mr. S. A. Rasheed, Project Director of GCWWMIIP, NWSDB.

Finally my heartfelt gratitude goes to my dear parents, who have been my mentors always supportive and urging me to go on.

TABLE OF CONTENTS

Cor	Contents Page				
AB	ABSTRACTi				
AC	KNOWL	EDGEMENTSiii			
TA	TABLE OF CONTENTSiv				
LIS	T OF TA	ABLES			
LIS	LIST OF FIGURES				
LIS	LIST OF ABREVIATIONSix				
1.0	1.0 INTRODUCTION				
1.1	BAC	KGROUND1			
	1.1.1	Introduction to Non-Revenue Water			
	1.1.2	Introduction to Billed and Unbilled Consumption			
	1.1.3	Introduction to Real and Apparent Water Losses			
	1.1.4	Passive (Reactive) and Active Leakage Detection			
	1.1.5	Introduction to District Metered Area (DMA) Concept4			
	1.1.6	NRW values in CMC			
1.2	PRO	3LEM DEFINITION6			
1.3	OBJE	CTIVES7			
1.4	MET	HODOLOGY7			
1.5	STUI	DY AREA8			
1.6	DAT	A USED			
1.7	SCO	РЕ10			
1.8	REPORT STRUCTURE				
2.0	LITERATURE REVIEW12				
2.1	INTR	ODUCTION			
2.2	WATER DISTRIBUTION NETWORK12				
2.3	UND	ERSTANDING LEAKAGE			
2.4	2.4 FACTS ABOUT LEAKS				
	2.4.1	Sources of Leaks			
	2.4.2	Infrastructure Condition14			
	2.4.3	The influence of pressure			

	2.4.4	Reported, unreported and background leaks16			
	2.4.5	Natural rate of leakage			
	2.4.6	Speed and quality of repairs			
2.5	REVIEW OF CMC DISTRIBUTION SYSTEM				
2.6	PER 0	CAPITA / UNIT DOMESTIC CONSUMPTION22			
2.7	CURI	RENT LEAKAGE MANAGEMENT PRACTICES			
2.8	DMA CONCEPT AS A LEAKAGE MANAGEMENT TOOL26				
3.0	METHODOLOGY				
3.1	STUDY AREA – BACKGROUND				
3.2	SAM	PLE			
3.3	DATA	A COLLECTION AND PREPARATION40			
	3.3.1	Digital Elevated Model41			
	3.3.2	Stream and River Layer41			
	3.3.3	Water Distribution Network42			
	3.3.4	Proposed Water Distribution Model for 204042			
3.4	MET	HODOLOGY OF ANALYSIS42			
	3.4.1	Methodology for Hydraulic Analysis42			
	3.4.2	Summary of the Methodology			
3.5	SOFT	WARE AND TOOLS USED			
3.6	DATA	A PROCESSING			
	3.6.1	Digital Elevation Model46			
	3.6.2	Demand Polygons and Demand Nodes46			
	3.6.3	Other Vector Layers and Satellite Images			
4.0	RESU	JLTS, ANALYSIS AND DISCUSSION47			
4.1	INTRODUCTION47				
4.2	THE	HYDRAULIC ANALYSIS47			
	4.2.1 and rem	Identification of suitable new boundary to sub divide the proposed DMA oval of cascade water supply			
	4.2.2	Changing pipe lines in 2040 Hydraulic Model49			
4.3	HYD	RAULIC ANALYSIS RESULTS51			
5.0	CON	CLUSIONS AND RECOMMENDATIONS			

5.1	CONCLUSIONS
5.2	RECOMMENDATIONS
REFE	RENCES

LIST OF TABLES

No.	Caption Page
Table 1	: NRW values for 2010 - 2012
Table 2	: Locations of Leakage Recorded in CI Pipes14
Table 3	: Composition of pipe materials in CMC water distribution network15
Table 4	: Ages of CI Pipes in CMC water distribution network
Table 5	: Total Number of Leaks Repaired in 2012
Table 6	: Population Projection for the CMC Area 2012 to 204021
Table 7	: Projected Water Loss Ratio
Table 8	: Estimated Average NRW
Table 9	: Existing Design Criteria on Unit Domestic Water Demand of NWSDB23
Table 1	0 : Proposed Unit Domestic Water Demand
Table 1	1 : Distribution zones and DMA numbers
Table 1	2 : Number of Connections in the proposed DMA according to 2012 total
conn	ection details provided by NWSDB
Table 1	3 : Number of Consumer Connections and Priority connections in distribution
zone	s
Table 1	4 : Projected water demand for Distribution zones
Table 1	5 : Collected Data Layers, Scales, Formats and the Source40
Table 1	6 : Number of Existing Connections to New DMA arrangement in this study 52
Table 1	7 : Validate of Minimum Pressure at Peak Hour Flow and elevation of that node
at the	Nodes having the minimum peak hour pressure in DMAs53
Table 1	8 : Validate of Demand at Peak Hour flow at Proposed Inlet Pipeline and
velo	tity of flow to DMAs

LIST OF FIGURES

No. Caption Page
Figure 1 : Typical DMA arrangement
Figure 2 : NRW values for 2010 – 2012
Figure 3 : Location Map of Study Area9
Figure 4 : Typical components of infrastructure in water distribution network
Figure 5 : Types of leakages in a water distribution network
Figure 6 : Types of leakages in a water distribution network
Figure 7 : Typical 24-hour leakage modeling based on minimum night flow analysis 19
Figure 8 : Existing Unit Domestic Water Consumption in Major Cities in Southeast
Asia in 200124
Figure 9 : Proposed distribution zones in CMC area
Figure 10 : Proposed 38 DMAs in CMC area
Figure 11 : Number of Consumer Connections and Priority connections in distribution
zones
Figure 12 : DEM of Elie House Distribution Zone
Figure 13 : Proposed 12 DMAs in Elie House Distribution Zone by Western Province
Metropolitan Area Water Supply Master Plan Update, 2013
Figure 14 : Proposed DMA arrangement for Elie House distribution zone
Figure 15 : Graphical Illustration of the Methodology Followed in the Entire Study 43
Figure 16 : The Methodology used for Hydraulic Analysis44
Figure 17 : Identified location for sub divide the proposed Elie House South West DMA
Figure 18 : Identified DMAs to remove the cascade water supply50
Figure 19 : Proposed DMA arrangement for Elie House distribution zone in this study
Figure 20 : Proposed DMA arrangement in this study for Elie House distribution zone
Figure 21 : Map on Proposed DMA arrangement in this study for Elie House
distribution zone for 2040

LIST OF ABREVIATIONS

Abbreviation

AC	-	Asbestos Cement
ALC	-	Active Leakage Control
AWWA	-	American Water Works Association
CI	-	Cast Iron
CMC	-	Colombo Municipal Council
DEM	-	Digital Elevation Model
DI	-	Ductile Iron
DMA	-	District Metered Area
ELL		Economic Level of Leaks
GCWWMIIP	-	Greater Colombo Water and Wastewater Management
		Investment Improvement Programme
GIS		Geographic Information System
GPS	-	Global Positioning System
HDPE	-	High-density Polyethylene
1/s	-	Litre per Second
m3/h	-	Cubic Meter per Second
mm	-	Millimetre
Ml	-	Million Litres
MS	Nalat Peters	Steel
inch	-	Inch
PE		Polyethylene
PLC	-	Passive Leakage Control
PMU	-	Project Management Unit
PVC	-	Polyvinylchloride
NRW	-	Non-Revenue Water
NWSDB	+	National Water Supply and Drainage Board

Abbreviation		
QEPAWBWC	-	Queensland Environmental Protection Agency and Wide
		Bay Water Corporation
SCADA	-	Supervisory Control and Data Acquisition
TIN	-	Triangular Irregular Network
UK	•	United Kingdom
USA	-	United States of America

1.0 INTRODUCTION

1.1 BACKGROUND

In recent years, water and energy conservation has become increasingly important for water utilities throughout the world. Policy makers and utility managers realise that reduction of Non-Revenue Water (NRW) is important from environmental, political and commercial points of view. Similar developments took place in Europe and Southeast Asian countries few years ago.

Presently the National Water Supply & Drainage Board (NWSDB) is the main water utilities infrastructure development authority in Sri Lanka. NWSDB is under no or little regulatory pressure to control water leakage. Therefore the NRW value is very high in the water distribution networks and leakage management is generally limited to passive leakage (reactive leakage) control such as responding to visible water leakages in the distribution system or auditing to water loss. That is responding to reported breaks or pressure drops, usually reported by customers or noted by the NWSDB staff while carrying out other duties. In normal situations, the overall level of leakage will continue to rise under Passive Leakage Management. The NRW reduction has become a major issue for the NWSDB because high level of NRW currently experienced in the water distribution network for Colombo Municipal Council (CMC) area.

Recent draughts, desalination of water resources (i.e. desalination close to the Ambatale Intake), higher production cost of water, and increasing competition over limited water resources has created pressure to reduce NRW volume such as water leakages in the water distribution pipe network. The NWSDB have historically suggested conservation of water usage, but water rights issues could necessitate mandated leakage targets and proactive leakage management.

According to Fanner (2007) NRW volume such as water leakages in the water distribution pipe network can be effectively reduced and controlled in a sustainable manner and the reduced leakage water can be viewed as a new source of water that will