See discussions, stats, and author profiles for this publication at: https://www.researchgate.net/publication/318528312

Sorption behavior of fluoride ions on Fe-Mg-Ce tri-metal composite

Conference Paper · December 2016

CITATIONS	5	READS	
0		10	
4 autho	rs, including:		
	Thilini Thathsara		Asitha Cooray
100	University of Sri Jayewardenepura	\sim	University of Sri Jayewardenepura
	3 PUBLICATIONS 0 CITATIONS		5 PUBLICATIONS 0 CITATIONS
	SEE PROFILE		SEE PROFILE
	Dilru Roshan Ratnaweera		
Contraction of the second seco	30 PUBLICATIONS 38 CITATIONS		
	SEE PROFILE		

Some of the authors of this publication are also working on these related projects:



USE OF METAL-COMPOSITE INCORPORATED/COATED BIO-POLYMER BEADS FOR THE REMOVAL OF FLUORIDE IONS FROM AQUEOUS MEDIA View project



Sorption behavior of fluoride ions on Fe-Mg-Ce tri-metal composite View project

All content following this page was uploaded by Thilini Thathsara on 19 July 2017.

Sorption behavior of fluoride ions on Fe-Mg-Ce tri-metal composite

Thathsara S.K.T¹, Cooray A. T²., Ratnaweera D. R¹., Kuruwita-Mudiyanselage T.D.^{1*}

Present Addresses: 1- Department of Chemistry, Faculty of Applied Science, University of Sri Jayewardenepura.

2- Central Instrumentation Facility, Faculty of Applied Science, University of Sri Jayewardenepura

ABSTRACT

Weathering of fluoride rich rocks and industrial processes such as electroplating and glass manufacturing result in accumulation of fluoride in natural water bodies. Fluoride is an essential micro nutrient to humans and animals in many aspects namely, strengthening of bones, prevention of tooth decay, and to regulate the human growth rate. The acceptable level of fluoride in drinking water is 1.5 mg/L as recommended by the World Health Organization. However, the recommended level of fluoride for tropical countries such as Sri Lanka is 1.0 mg/L. Excess amount of fluoride ions in drinking water causes health risks such as skeletal and dental fluorosis, cancers, infertility and thyroid disorder. In general, the drinking water sources in the intermediate and dry zones in Sri Lanka is rich in Fluoride. Therefore, millions of lives are at the risk of developing fluoride developing diseases. On that regard, removal of fluoride ions from drinking water have gained much attention in research community.

A wide variety of novel adsorbents have been developed to remove fluoride ions from aqueous medium. In this work 1:1:1 ratio of tri-metal composites of Fe-Mg-Al, Fe-Mg-Zn, Al-Mg-Ce and Fe-Mg-Ce were synthesized using co-precipitation method for the removal of fluoride ions from aqueous solutions with the efficiencies (the amount of fluoride ions adsorbed per unit) of 0.275±0.01, 1.496±0.259, 2.016±1.553 and 2.554±0.0079 mg/g respectively. As reported above, the highest amount of fluoride adsorbed per unit of fluoride ions were observed for the iron-magnesium-cerium tri-metallic composite. Therefore, further studies were carried out to improve its efficiency by varying the solution pH, contact time and the molar ratios of metals in the composite. The adsorption process was highly pHdependent. The maximum amount of fluoride adsorbed per unit of the Fe-Mg-Ce tri-metal composite was determined to be 48.31 mg/g at pH 7. Rapidly adsorption of fluoride was observed within the first sixty minutes and equilibrium was established within 5 hours. The fluoride removal efficiencies for Fe:Mg:Ce composites with molar ratios of 1:1:1, 1:1:2, 1:2:1 and 2:1:1 were 2.55 0± 0.008, 48.310 ±0 .079, 17.230 ± 0.263 and 23.380±0.090 mg/g at pH 7.00 respectively. These composites were further studied using FT-IR techniques and XRD.

Acknowledgement: Financial assistance by University of Sri Jayewardenepura, research grant ASP/01/RE/SCI/2015/31